
GEBERIT

Geberit WC flush control with electronic flush actuation, mains operation, dual flush, flush plate Sigma10, automatic/touchless/manual

t⊢ T





Example image

Application purposes

- For public and semipublic areas
- · For releasing a dual flush
- · For solid and drywall construction
- For touchless flush actuation of Geberit Sigma concealed cisterns 12 cm
- · Not suitable for use with Geberit inserts for in-cistern block
- · Not suitable for less-abled installation

Characteristics

- · Touchless manual flush actuation
- Automatic flush actuation
- Touchless flush actuation for single or dual flush by moving hand toward sensor
- Manual flush actuation via flush plate
- Screwable flush plate
- Power supply via power supply unit
- External power supply unit
- Transformation of mains voltage to extra-low voltage, 4.1 V DC
- · Operation with extra-low voltage, no mains voltage in cistern
- With push-fit connection with cross-polarity protection
- · Infrared user detection with background fade-out
- Self-adjusting IR sensor
- Reliable IR distance detection
- Interval flush preset
- Adjustable interval flush
- Preflush can be set
- Minimum detection time can be set
- Compatible with Geberit Service Handy
- Functions can be set and queried with the Geberit Service Handy

- Flush actuation can be deactivated via Geberit Clean Handy
- Low-noise lifting mechanism
- Electrical lifting device, self-calibrating
- Vandal-resistant
- Easy maintenance and cleaning

Technical data

Protection degree	IP45
Nominal voltage	85-240 V AC
Mains frequency	50-60 Hz
Operating voltage	4.1 V DC
Interval flush, adjustment range	1-168 h
Interval flush, factory setting	24 h
Interval flush time, adjustment range	1-200 s
Interval flush time, factory setting	1 s
Detection time, adjustment range	1-60 s
Detection time, factory setting	7 s

Scope of delivery

- Flush plate Sigma10
- · Mounting frame with infrared control, premounted
- Protection plate
- · Support block with servomotor and lifting device, premounted
- Actuator rod
- · Fastening material

To order additionally

 Geberit installation set for WC flush controls with electronic flush actuation

Art. no.	Colour / surface	Material designation	В	Н	т
115.890.SN.5	Plate and button: brushed Design ring: polished	Stainless steel	24.6 cm	16.4 cm	1.5 cm

Accessories

- Geberit Service Handy
- Geberit Clean Handy



• Requires transformer 115.861.00.1