



Geberit Monolith sanitary module for floor-standing WC, 114 cm



Example image



Application purposes

- For floor inlets
- For renovations, conversions and new buildings
- For wall inlets with an inlet height of 18 cm
- For replacing floor-standing WCs with concealed cistern with maximum service opening height < 109 cm
- For replacing low-level exposed cisterns
- For replacing half-high level exposed cisterns
- For replacing floor-standing WCs with close-coupled exposed cistern
- For connecting Geberit AquaClean Sela floor-standing WC
- For connecting Geberit AquaClean Tuma WC complete solution, floor-standing WC
- For connecting Geberit AquaClean WC enhancement solutions, with accessories
- For replacing pressure flushing valves
- For mounting on finished floors
- For installation in front of drywalls or solid walls

Characteristics

- Dual flush
- Compensation of dimensional tolerances possible
- Front cladding made of glass (ESG)
- Cistern, fully insulated against condensation
- Side cladding made of aluminium brushed
- Self-supporting

- Adjustable flush volume
- Water supply connection on the rear centre
- Water supply connection on the left/right possible with accessories
- Water supply connection on the bottom

Technical data

| | |
|--|------------|
| Flow pressure | 0.1-10 bar |
| Maximum operating temperature, water | 25 °C |
| Flush volume, factory setting | 6 and 3 l |
| Flush volume large, adjustment range | 4.5 / 6 l |
| Flush volume small | 3 l |
| Calculated flow rate | 0.11 l/s |
| Minimum flow pressure for calculated flow rate | 0.5 bar |

Scope of delivery

- Water supply connection set with 2 angle stop valves, 1/2"
- Flush bend extension 160 mm
- Connection bend made of PP, ø 90 mm
- Sleeve made of EPDM, ø 44 / 55 mm
- Adaptor socket made of PE-HD, ø 90 / 110 mm
- Fastening material
- Base cover
- Fastening material for drywall

| Art. no. | Colour / surface | B | H | T |
|--------------|------------------|---------|--------|---------|
| 131.033.SQ.5 | umber / glass | 50.5 cm | 114 cm | 10.6 cm |
| 131.033.SI.5 | white / glass | 50.5 cm | 114 cm | 10.6 cm |
| 131.033.TG.5 | sand / glass | 50.5 cm | 114 cm | 10.6 cm |
| 131.033.SJ.5 | black / glass | 50.5 cm | 114 cm | 10.6 cm |

Accessories

- Set of fixing bolts made of aluminium, for Geberit Monolith side cladding
- Conversion set for Geberit AquaClean WC enhancement solutions
- Lateral water supply connection set for Geberit Monolith sanitary module for WC



- Glass thickness 8 mm