



Geberit Monolith Plus sanitary module for wall-hung WC, 114 cm



Example image



Application purposes

- For renovations, conversions and new buildings
- For wall inlets with inlet height > 23 cm
- For replacing low-level exposed cisterns
- For replacing half-high level exposed cisterns
- For replacing wall-hung WCs with close-coupled exposed cistern
- For replacing wall-hung WCs with pressure flushing valve
- For replacing wall-hung WCs with concealed cistern with maximum service opening height < 109 cm
- For Geberit AquaClean WC complete solutions
- For connecting Geberit AquaClean WC enhancement solutions, with accessories
- For mounting on finished floors
- For installation in front of drywalls or solid walls
- For compensating the offset between WC connections and wall drains using a stepped straight connector for wall-hung WCs

Characteristics

- Dual flush
- Compensation of dimensional tolerances possible
- Height-adjustable up to 7 cm
- Front cladding made of glass (ESG)
- Fastening height WC ceramic appliance 35 ± 1 cm
- Cistern, fully insulated against condensation
- Side cladding made of aluminium brushed
- Self-supporting
- Adjustable flush volume
- Soft-touch buttons for flush actuation and odour extraction
- Orientation light and odour extraction activated when a user approaches
- Orientation light can be set in seven colours
- User detection range can be set
- Day/night detection can be set for orientation light
- Odour extraction unit with ceramic honeycomb filter can be installed without tools
- Ceramic honeycomb filter for odour neutralisation can be replaced without tools
- Odour extraction unit automatically switches off after a predefined running time

- Operation with extra-low voltage, no mains voltage in cistern
- Mains connection with flexible three-wire sheathed cable
- Water supply connection on the rear centre
- Water supply connection on the left/right possible with accessories
- Water supply connection on the bottom

Technical data

Protection class	I
Protection degree	IPX4
Nominal voltage	100-240 V AC
Mains frequency	50-60 Hz
Operating voltage	4.1 V DC
Power consumption	5 W
Flow pressure	0.1-10 bar
Maximum operating temperature, water	25 °C
Flush volume	6 l
Flush volume small	3 l
Calculated flow rate	0.11 l/s
Minimum flow pressure for calculated flow rate	0.5 bar

Scope of delivery

- Water supply connection set with 2 angle stop valves, 1/2"
- Flush bend extension 160 mm
- Sleeve made of EPDM, ø 44 / 55 mm
- Straight connector made of PE-HD, ø 90 mm
- Adaptor socket made of PE-HD, ø 90 / 110 mm
- 2 threaded rods M12
- Sound insulation set
- Female socket for mains connection
- Power supply unit
- Base cover
- Fastening material for drywall
- Fastening material
- Fastening material for installation in front of concealed cisterns

Art. no.	Colour / surface	B	H	T
131.231.SQ.5	umber / glass	50.5 cm	114 cm	10.6 cm
131.231.SI.5	white / glass	50.5 cm	114 cm	10.6 cm
131.231.TG.5	sand / glass	50.5 cm	114 cm	10.6 cm

Art. no.	Colour / surface	B	H	T
131.231.SJ.5	black / glass	50.5 cm	114 cm	10.6 cm

Accessories

- Geberit straight connector set for wall-hung WC, stepped by 3 cm
- Geberit straight connector set for wall-hung WC, stepped by 5 cm
- Geberit straight connector set for wall-hung WC, stepped by 7 cm
- Geberit outlet mounting box
- Conversion set for Geberit AquaClean WC enhancement solutions
- Lateral water supply connection set for Geberit Monolith sanitary module for WC



-
- Glass thickness 8 mm